Product datasheet

Specifications





Standard closing voltage release XF, MasterPact NT drawout, 200/250VDC, 200/250VAC

47443

Main

Range	MasterPacT
Range Of Product	MasterPact NT
Device Short Name	XF
Product Or Component Type	Voltage release
Device Application	Control
Voltage Release Type	Closing coil Instantaneous voltage release
Control Type	Standard
[Uc] Control Circuit Voltage	200250 V AC 50/60 Hz 200250 V DC
Circuit Breaker Mounting Mode	Drawout
Range Compatibility	Masterpact MasterPact NT

Complementary

Operating Threshold	0.851.1 Un closing
Response Time	55 ms +/- 10 %
Supply Holding Power	4.5 VA

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	1.167 kg

Contractual warranty

Warranty

18 months

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information