

# Product datasheet

Specifications



## Add-on contact block, TeSys Deca Frame 2/3, 2NO, side, for GV2/ GV3 (except GV3ME)

GVAN20

### Main

<b>Range</b>	TeSys TeSys Deca
<b>Device Short Name</b>	GVAN
<b>Product Or Component Type</b>	Auxiliary contact block
<b>Product Compatibility</b>	GV2ME GV3P GV2RT GV2LE GV2L GV3L GV2P
<b>Mounting Location</b>	Left side
<b>Pole Contact Composition</b>	2 NO

### Complementary

<b>[Ui] Rated Insulation Voltage</b>	600 V conforming to UL 508 690 V conforming to IEC 60947-1 600 V conforming to CSA C22.2 No 14
<b>[Ue] Rated Operational Voltage</b>	48...690 V AC 24...240 V DC
<b>[Ith] Conventional Free Air Thermal Current</b>	6 A
<b>Mechanical Durability</b>	100000 cycles
<b>Minimum Switching Current</b>	5 mA
<b>Minimum Switching Voltage</b>	17 V
<b>Protection Type</b>	GB2CB... circuit breaker GG fuse 10 A
<b>Rated Operational Power In Va</b>	300 VA at 48 V AC-15 - electrical durability: 100000 cycles 414 VA at 690 V AC-15 - electrical durability: 100000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 100000 cycles 500 VA at 500 V AC-15 - electrical durability: 100000 cycles 650 VA at 440 V AC-15 - electrical durability: 100000 cycles 720 VA at 230...240 V AC-15 - electrical durability: 100000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 100000 cycles
<b>Rated Operational Power In W</b>	120 W at 240 V DC-13 - electrical durability: 100000 cycles 140 W at 110 V DC-13 - electrical durability: 100000 cycles 140 W at 24 V DC-13 - electrical durability: 100000 cycles 180 W at 60 V DC-13 - electrical durability: 100000 cycles 240 W at 48 V DC-13 - electrical durability: 100000 cycles
<b>Tightening Torque</b>	1.4 N.m - on screw clamp terminals
<b>Height</b>	89 mm
<b>Width</b>	9.3 mm

Depth	66 mm
Net Weight	0.05 kg
Colour	Dark grey

## Environment

Environmental Characteristic	Normal environment
Product Certifications	UKCA

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	9.400 cm
Package 1 Width	9.800 cm
Package 1 Length	15.000 cm
Package 1 Weight	41.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	9.500 cm
Package 2 Width	9.800 cm
Package 2 Length	15.000 cm
Package 2 Weight	461.000 g
Unit Type Of Package 3	S02
Number Of Units In Package 3	60
Package 3 Height	15.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	3.050 kg

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant

[EU RoHS Declaration](#)

**China Rohs Regulation**

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

**Environmental Disclosure**

[Product Environmental Profile](#)

**Weee**

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Circularity Profile**

[End of Life Information](#)

GVAN20

